



SERIES 2300-L

ROTATING CONTROL DEVICE



The Washington Series 2300-L is the lowest profile Rotating Control Device that we offer and is ideal for use on top-drive or workover rigs. This unit is designed to seal off the drill string components continuously and divert all debris and drill cuttings away from the rig. The 2300-L Series Control Device utilizes our 4010-V stripper rubber and will seal off all drill steel from 2" to 8" OD. Whether you are drilling gas, oil or geothermal wells, Washington Rotating can accommodate all of your diverter needs.



Nominal Flange	A	B	C	D	E	Outlet	Ring Gasket
7 ¹ / ₁₆ "-3000	26 ⁷ / ₈ "	7 ¹ / ₁₆ "	8 ¹ / ₈ "	21"	11 ⁵ / ₈ "	7" - 8RD	R-45
7 ¹ / ₁₆ "-5000	26 ⁷ / ₈ "	7 ¹ / ₁₆ "	8 ¹ / ₈ "	21"	11 ⁵ / ₈ "	7" - 8RD	R-46
9"-3000	26 ⁷ / ₈ "	9"	8 ¹ / ₈ "	20"	11 ⁵ / ₈ "	7" - 8RD	R-49
9"-5000	26 ⁷ / ₈ "	9"	8 ¹ / ₈ "	20"	11 ⁵ / ₈ "	7" - 8RD	R-50
11"-3000	21 ¹ / ₈ "	11 ¹ / ₈ "	8 ¹ / ₈ "	16"	6 ⁵ / ₈ "	7" - 8RD	R-53
11"-5000	21 ¹ / ₈ "	11 ¹ / ₈ "	8 ¹ / ₈ "	16"	6 ⁵ / ₈ "	7" - 8RD	R-54
13 ⁵ / ₈ "-3000	21 ¹ / ₈ "	13 ¹ / ₂ "	8 ¹ / ₈ "	16"	7 ¹ / ₈ "	7" - 8RD	R-57
13 ⁵ / ₈ "-5000	21 ¹ / ₈ "	13 ¹ / ₂ "	8 ¹ / ₈ "	16"	7 ¹ / ₈ "	7" - 8RD	BX-160

REV 4/15

Western Diverter
 p (970) 245-1089 | f (970) 245-1589
 2453 Industrial Blvd.
 Grand Junction, CO 81505
 www.westerndiverter.com
 info@westerndiverter.com

Our test pressures have been established through controlled test procedures. As a result of the ever-changing environment of well drilling operations along with wear and tear on equipment, which erodes longevity and safe operating parameters, Washington Rotating Control Heads, Inc., its Business Units, Agents and Affiliates make no warranty either expressed or implied on the test pressures contained herein. Washington Rotating Control Heads, Inc. does not under any circumstances recommend that its rotating control devices be used as primary blow out prevention equipment.